



**National Information & Communications Technology Authority**

**RADIOCOMMUNICATION CLASS LICENSE**

- **LOW INTERFERENCE POTENTIAL DEVICES (LIPD) OR SHORT RANGE DEVICES (SRD) MINIMUM REQUIREMENTS**

Date of Revision: 19 May 2026

## Table of Contents

<b>1</b>	<b>Name of Class Licence</b>	<b>2</b>
<b>2</b>	<b>Commencement</b>	<b>2</b>
<b>3</b>	<b>Revocation</b>	<b>2</b>
<b>4</b>	<b>Short Range RF Devices (SRD) Compliance Requirements</b>	<b>2</b>
<b>5</b>	<b>Interpretation</b>	<b>3</b>
<b>6</b>	<b>Class Licence</b>	<b>5</b>
<b>7</b>	<b>Standards and international instruments</b>	<b>6</b>
	<b>Schedule 1: Transmitters</b>	<b>8</b>
	<b>Schedule 2: International instruments that apply to a transmitter</b>	<b>26</b>

## **1. Name of Class Licence**

This Class Licence is the Radiocommunications (Low Interference Potential Devices) Class Licence 2026, made under Section 176 of the National Information and Communication Technology Act, 2009.

## **2. Commencement**

This Class Licence commences on gazettal.

## **3. Revocation**

The Radiocommunications (Low Interference Potential Devices) Class Licence 2016 is revoked.

## **4. Short Range RF Devices (SRD) Compliance Requirements**

- (1) Short Range Devices (Low Power RF transmitters and associated RF receivers) are categorised by NICTA as “Low Interference Potential Devices” (LIPD’s), as they are considered to pose a low risk of interference to other RF communications devices.
- (2) NICTA adopts the Radiocommunications (Low Interference Potential Devices) Class Licence 2025 made by the Australian Communications and Media Authority (ACMA) but has made minor changes to the text to align the Radiocommunication (LIPD) Class Licence 2026 with existing NICTA regulations to manage the Short Range Devices RF spectrum in Papua New Guinea (PNG).
- (3) Under Section 176 of the NICT Act, this Radiocommunication Class Licence authorises a Person to operate a wide range of low-power radiocommunications devices in predefined segments of the radiofrequency spectrum. This Class Licence does not require licence applications or licencing fees to be paid. All users of the same occupied spectrum do so on an uncoordinated shared basis, and if interference occurs, the Person responsible must cease or modify transmissions in order to resolve the interference or as directed by NICTA.
- (4) To ensure compliance with the LIPD Class Licence arrangements the following process is required:
  - Complete and send a Declaration of Conformity (DoC) to NICTA: and
  - Complete the Type Approval Application Form and submit it to NICTA together with the required product test information through the NICTA Online Type Approval System.

## 5. Interpretation

(1) In this Class Licence:

**Act** means the National Information and Communications Technology Act 2009.

**ARPANSA Standard** means the Radiation Protection Standard for Maximum Exposure Levels to Radiofrequency Fields – 3 kHz to 300 GHz, published by the Australian Radiation Protection and Nuclear Safety Agency.

Note: The ARPANSA Standard is available from the Australian Radiation Protection and Nuclear Safety Agency website: <http://www.arpansa.gov.au>.

**Broadcasting Service** has the meaning given by the Broadcasting Corporation Act 1973 (including any successor instruments);

**Coverage Area**, for a broadcasting station, means:

- (a) if the station is used to provide a commercial television broadcasting service or community television broadcasting service – the area within the licence area where the median field strength  $E(50,50)$  of the transmission made by the station, at 10 metres above ground level, is at least the specified limit; and
- (b) in any other case – the area where the median field strength  $E(50,50)$  of the transmission made by the station, at 10 metres above ground level, is at least the specified limit.

**Column numbering:** For the purposes of interpreting Schedule 1 and Schedule 2, the numbering of columns begins at zero (0), where Column 0 is the Item Number.

**Contention-based Protocol** means a channel access method that requires a transmitter to monitor the radio channel and to defer transmission when it detects that the channel is occupied, for example, by using listen-before-talk (LBT) or clear channel assessment (CCA) techniques.

**DAB** means digital audio broadcasting.

**Declaration of Conformity (DoC)** has the same meaning as defined in the ICT Equipment Type Approval Rule 2022, including any future updated or successor instrument that replaces it. All references to DoC in this instrument must be interpreted in accordance with that Rule.

**EIRP** means equivalent isotropic radiated power.

**ERP** means effective radiated power.

**ETSI** means the European Telecommunications Standards Institute.

**FCC** means the United States of America Federal Communications Commission.

**Field Strength** means the intensity of the electromagnetic field produced by a transmitter, at a particular distance from the transmitter, measured in:

- (a) in relation to the electric component of the field –  $V/m$ , where **V** means volts and **m** means metres; and
- (b) in relation to the magnetic component of the field –  $A/m$ , where **A** means amperes and **m** means metres.

**Infrared Transmitter** means a radiocommunications transmitter having a radio emission in the frequency range 187.5 THz to 420 THz.

**International Instrument** means an international technical standard or performance indicator.

**Licence Area** means:

- (a) in relation to a broadcasting station used to provide a commercial television broadcasting service – the licence area designated for the relevant commercial television broadcasting licence;
- (b) in relation to a broadcasting station used to provide a community broadcasting service, other than a service provided under a temporary community broadcasting licence – the licence area designated for the relevant community television broadcasting licence; and
- (c) in relation to a broadcasting station used to provide a community broadcasting service provided under a temporary community broadcasting licence – the licence area designated for the relevant temporary community broadcasting licence.

**Maximum EIRP**, for a transmitter mentioned in column 1 of an item in Schedule 1, means the largest amount of EIRP, mentioned in column 3 of that item, which may be radiated by the transmitter in any direction under normal operating conditions.

**Person** has the same meaning in the Act.

**Power spectral density (PSD)** means the EIRP of a transmitter expressed as power per unit bandwidth and measured over a 1 MHz reference bandwidth.

**Radiated Power** means the power that is emitted from any of the following:

- (a) an antenna that is an integral part of the transmitter;
- (b) an antenna that is connected to the transmitter;
- (c) the surface of a specified enclosure containing the antenna; and
- (d) for an item in Schedule 1 that mentions an opening and an underground environment – the opening to the underground environment.

**Radio Broadcasting Service** means a broadcasting service that provides radio programs.

**Radio Local Area Network (RLAN)** means a transmitter used for wireless data networking within a localized area.

**Significant Event** means an event at a location or locations specified in a notice approved by the Board of NICTA.

**Specified Limit**, in relation to the median field strength E(50,50) of a transmission made by a station, means:

- (a) for a transmission in the band 174–230 MHz, in respect of a television broadcasting service – 44 dBu V/m;
- (b) for a transmission in the band 174–230 MHz, in respect of a digital radio broadcasting service – 63 dBu V/m;
- (c) for a transmission in the band 520–610 MHz – 50 dBu V/m; and
- (d) for a transmission in the band 610–694 MHz – 54 dBu V/m.

**Television Broadcasting Service** means a broadcasting service that provides television programs.

**Transmitter Power** means the power at the output of the transmitter going to the antenna.

## 6. Class Licence

- (1) This Class Licence authorises a Person to operate a transmitter included in a class of transmitters mentioned in column 1 of an item in Schedule 1, subject to the following conditions:
  - (a) the transmitter must be operated:
    - (i) on a frequency, or within a range of frequencies, mentioned in column 2 of the item;
    - (ii) at a radiated power that does not exceed the maximum EIRP mentioned in column 3 of the item; and
    - (iii) in accordance with the limitations (if any) mentioned in column 4 of the item;
  - (b) the transmitter, whether on its own or in operation with one or more other transmitters, must not cause interference to the operation of radiocommunications services.
- (2) The following requirements must be construed in accordance with the interpretative provisions (if any) of a standard or international instrument mentioned in column 4 of an item in Schedule 1:
  - (a) a frequency or range of frequencies mentioned in column 4 of the item; and
  - (b) the maximum EIRP mentioned in column 3 of the item.
- (3) The permitted operating frequency band in column 2 of an item in Schedule 1 must not be construed in accordance with the interpretative provisions (if any) of a standard or international instrument mentioned in column 4 of the item.

**Note 1** A transmitter operated under this Class Licence can be expected to be operating in parts of the radiofrequency spectrum used by other radiocommunications devices. A receiver tuned to the transmitter will not be afforded protection from interference caused by other radiocommunications devices. A low interference potential device operated under this Class Licence is generally not expected to suffer interference; however, an individual low interference potential device may experience interference arising from the particular circumstances of the device's operation.

**Note 2** In accordance with the requirements of footnotes 5.138 and 5.150 in the *Papua New Guinea Table of Radiofrequency Allocations 2025*, a low interference potential device will not be afforded protection from interference that may be caused by industrial, scientific and medical (**ISM**) applications in the ISM bands 13.553 MHz – 13.567 MHz, 26.957 MHz – 27.283 MHz, 40.66 MHz – 40.70 MHz, 2 400 MHz – 2 500 MHz, 5 725 MHz – 5 875 MHz and 24 000 MHz – 24 250 MHz

**Note 3** Some transmitters operated under this Class Licence must meet additional physical or technical requirements outside the scope of this Class Licence.

**Note 4** The operation of a device with an external antenna, other than an antenna supplied with the device, may result in a breach of the conditions of this Class Licence. An **external antenna** is a removable antenna that is not an integral antenna. An **integral antenna** is an antenna that is permanently fixed to a device, or which is

intended for direct attachment to a fixed connector on the device, without the use of an external cable.

**Note 5** A transmitter, or group of transmitters, capable of operating simultaneously on frequencies in more than one permitted operating frequency band (mentioned in column 2 of the table in Schedule 1) must comply with the Radiocommunications (Electromagnetic Radiation – Human Exposure) Standard 2014 for the total power that is emitted.

**Note 6** The applicable requirements relating to electromagnetic radiation regulatory arrangements are as prescribed by NICTA from time to time, including under the EMF Exposure Limit Guideline 2018.

## **7. Standards and international instruments**

**(1)** A Person must not operate a transmitter under this Class Licence unless the transmitter complies with each applicable instrument for the transmitter.

**(2)** Subsection (1) does not apply if:

- (a) the Person operates the transmitter in accordance with a permit; or
- (b) the transmitter:
  - (i) is imported into Papua New Guinea solely for use in connection with a significant event;
  - (ii) if there is a requirement that the transmitter is tested or inspected before it is used in Papua New Guinea – meets the requirement;
  - (iii) if there are conditions or requirements imposed on the use of the transmitter in Papua New Guinea – complies with all of those conditions or requirements;
  - (iv) is used in Papua New Guinea only at the location of the significant event; and
  - (v) is used in Papua New Guinea only for the duration of the significant event.

**(3)** In this section, applicable instrument, in relation to a transmitter, means either:

- (a) a standard that applies to the transmitter; or
- (b) an international instrument that applies to the transmitter that is mentioned in column 2 of an item in Schedule 2 for a transmitter mentioned in column 1 of the item.

**Note 1** The upper and lower limits of the permitted operating frequency band mentioned in column 2 of an item in Schedule 1 apply to a transmitter mentioned in column 1 of the item, irrespective of any frequency limits specified in any applicable instrument for the transmitter.

**Note 2** The full titles and sources for international instruments referenced in column 4 (Limitations) of the table in Schedule 1 are set out in Schedule 2 to ensure clarity of compliance requirements.

The full titles and sources for an international instrument that is an applicable instrument mentioned in column 4 (Limitations) of the table in Schedule 1 are set out in Schedule 2.

**Note 3** If a device document is stamped with the Regulatory Compliance Mark or the N-Tick compliance mark, it means that the device supplied complies with any standard that applies to the device.

**Note 4** A reference to a *standard* is to a standard made or recognized by NICTA. This Class Licence requires transmitters to comply with instruments that specify performance requirements, including instruments produced by the European Telecommunications Standards Institute (ETSI).

**Note 5** An applicable instrument for a transmitter may be amended over time or may incorporate amendments to other instruments. A Person who wishes to operate a transmitter should check the NICTA's standards or other instruments to determine which version of the applicable instrument applies to the transmitter.

(4) A Person must not operate a transmitter or group of transmitters under this Class Licence if the electromagnetic radiation emitted by the transmitter or group of transmitters exceeds the general public exposure limits specified in the NICTA *EMF Exposure Limit Guideline 2018* in a place accessible by the public.

**Note 1** A transmitter with an integral antenna must not be supplied unless it complies with the exposure limits specified in the ARPANSA Standard. A transmitter, whether on its own or included in a group of transmitters to which, after it is supplied, a Person attaches an external antenna (that is, an antenna other than an integral antenna), located in an area accessible to the public must meet exposure limits specified in the NICTA *EMF Exposure Limit Guideline 2018*. An **integral antenna** is an antenna that is permanently fixed to a device, or which is intended for direct attachment to a fixed connector on the device, without the use of an external cable.

**Note 2** A transmitter with a dedicated antenna (as defined by applicable instruments produced by ETSI) is equivalent to a transmitter with an integral antenna for the purpose of the ARPANSA Standard.

**Note 3** Australia/New Zealand Standard AS/NZS 2211.10:2004 details the requirements that are necessary to protect Persons from radiation from laser devices, the use of many of which is authorised by this Class Licence.

**Note 4** Where a transmitter or group of transmitters, is capable of operating simultaneously on frequencies in more than one operating frequency band mentioned in column 2 of the table in Schedule 1 in places accessible by the public, the general public exposure limits specified in the NICTA *EMF Exposure Limit Guideline 2018* apply to the total power that is emitted.

## Schedule 1 Transmitters

Item	Class of transmitter	Permitted operating frequency band (MHz) (lower limit exclusive, upper limit inclusive)	Maximum EIRP	Limitations
<b>Transmitters for non – specific applications</b>				
1	All transmitters	0.000–0.014	200 $\mu$ W	
2	All transmitters	0.014–0.01995	50 $\mu$ W	
3	All transmitters	0.02005–0.048	43 $\mu$ W (see note 1)	
4	All transmitters	0.048–0.07	7.5 $\mu$ W (see note 1)	
5	All transmitters	1. 0.07 - 0.16	3 $\mu$ W (see note 1)	
6	All transmitters	0.16 – 0.19	1 $\mu$ W	
7	All transmitters	(a) 0.19–0.285 (b) 0.325–0.415	500 nW (see Note 1)	
8	All transmitters	3.025–3.155	7.5 nW	
9	All transmitters	3.5–3.7	30 pW	
10	All transmitters	(a) 3.7–3.95 (b) 4.438–4.65	7.5 nW	
11	All transmitters	13.553–13.567	100 mW	
12	All transmitters	24–24.89	10 mW	
13	All transmitters	26.957–27.283	1 W	<ol style="list-style-type: none"> <li>1. Separation of the operating frequency from the centre frequency of any adjacent citizen band radio channel must be at least 5 kHz.</li> <li>2. The emission bandwidth must not exceed 10 kHz.</li> </ol>

14	All transmitters	(a) 29.7–29.72 (b) 30–30.0625 (c) 30.3125–31 (d) 36.6–37 (e) 39–39.7625 (f) 40.25–40.66	100 mW	
15	All transmitters	40.66–41	1W	
16	All transmitters	54–56	2.5mW	
17	All transmitters	(a) 70–70.24375 (b) 77.29375–77.49375 (c) 150.7875–152.49375 (d) 173.29375–174	100 mW	
18	All transmitters	(a) 225–242 (b) 244–267 (c) 273–303.95 (d) 304.05–328.6 (e) 335.4–399.9	10 $\mu$ W	
19	All transmitters	433.05–434.79	25 mW	
20	All transmitters	915–928	3 mW	
21	All transmitters	2400–2483.5	10 mW	
22	All transmitters	5725–5875	25 mW	
23	All transmitters	(a) 10500–10550 (b) 24000–24250 (c) 61000–61500	100mW	

<b>Wireless microphones and other wireless audio equipment, including earpieces and wireless speaker transmitters</b>				
<b>Item</b>	<b>Class of transmitter</b>	<b>Permitted operating frequency band (MHz) (lower limit exclusive, upper limit inclusive)</b>	<b>Maximum EIRP</b>	<b>Limitations</b>
24	Auditory assistance transmitters	3.155–3.4, with a carrier frequency of: (a) 3.175; (b) 3.225; (c) 3.275; or (d) 3.325	60 $\mu$ W	
25	Auditory assistance transmitters	(a) 41–42, with a carrier frequency of: (i) 41.55; (ii) 41.65; (iii) 41.75; (iv) 41.85; or (v) 41.95 (b) 43–44, with a carrier frequency of: (i) 43.05; (ii) 43.15; (iii) 43.25; or (iv) 43.35 (c) 43.45	1.3 mW	
26	Wireless audio transmitters and auditory assistance transmitters	88–108	10 $\mu$ W	(a) Emission must be frequency modulated and have a maximum bandwidth of 180 kHz. (b) Transmission in a broadcasting services bands radio channel must not originate in the licence area of a radio broadcasting station (including a repeater or translator station) operating in the same channel.

27	Wireless audio transmitters	174–230	50mW(~30.5 mW ERP)	(a) Emission must have a maximum bandwidth of 330 kHz. (b) Transmission in a broadcasting services bands channel must not originate in the coverage area of a broadcasting station or datacasting service station (including a repeater or translator station) operating in the same channel.
28	Wireless audio transmitters	520–694	100 mW (~60.95 mW ERP)	(a) Emission must be frequency modulated and have a maximum bandwidth of 330 kHz. (b) Transmission in a broadcasting services band channel must not originate in the coverage area of a broadcasting station or datacasting service station (including a repeater or translator station) operating in the same channel.
29	Digitally modulated wireless audio transmitters	520–694	100 mW (~60.95 mW ERP)	(a) Emission must have a maximum bandwidth of 330 kHz. (b) Transmission in a broadcasting services band channel must not originate in the coverage area of a broadcasting station or datacasting service station (including a repeater or translator station) operating in the same channel.

30	Wireless audio transmitter	1785–1800	100 mW (~60.95 mW ERP)	(a) The transmitter must comply with ETSI Standard EN 300 422. (b) The transmitter must not be operated on a carrier frequency within 1 MHz of 1785 MHz. (c) The transmitter must only be operated indoors on a frequency below 1790 MHz.
31	Indoor wireless audio transmitters	520–694	100 mW (~60.95 mW ERP)	(a) The transmitter must only be operated indoors. (b) The transmitter must comply with either: (i) ETSI Standard EN 301 357; or (ii) ETSI Standard EN 300 422.

**Medical telemetry and telecommand transmitters**

Item	Class of transmitter	Permitted operating frequency band (MHz) (lower limit exclusive, upper limit inclusive)	Maximum EIRP	Limitations
32	Biomedical telemetry transmitters	174–230	10 $\mu$ W	
33	Medical implant communications system transmitters (see Note 2)	402–405	See limitation (a)	(a) The maximum EIRP is 25 $\mu$ W outside the body. (b) The transmitter must comply with either: (i) ETSI Standard EN 301 839.

34	Medical implant communications systems transmitters (see Note 2)	(a) 401–402 (b) 405–406	See limitation (a)	(a) The maximum EIRP is 25 $\mu$ W outside the body. (b) The transmitter must comply with ETSI Standard EN 302 537.
35	Biomedical telemetry transmitters	520–668	11 mW	Transmission in a broadcasting services bands channel must not originate in the coverage area of a broadcasting station or datacasting service station (including a repeater or translator station) operating in the same channel.

**General telemetry and telecommand transmitters**

Item	Class of transmitter	Permitted operating frequency band (MHz) (lower limit exclusive, upper limit inclusive)	Maximum EIRP	Limitations
36	Telecommand or telemetry transmitters	472.0125–472.1125	100 mW	
37	Telecommand or telemetry transmitters	(a) 0.07–0.119 (b) 0.135–0.160	10 mW	
38	Telecommand or telemetry transmitters	0.119–0.135	1.5 W	
39	Telecommand or telemetry transmitters	0.160–0.190	See limitation	ETSI EN 300 330 (V2.1.1 or later) — Short Range Devices; radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems 9 kHz to 30 MHz (see

				Annex J for relevant limits and transmitter emission requirements covering 160–190 kHz)
40	Telecommand or telemetry transmitters	(a) 2400–2450 (b) 5725–5795 (c) 5815–5875	1 W	
41	Telecommand or telemetry transmitters	5795–5815	2 W	

**Radiofrequency Identification (RFID) tags and associated transmitters**

<b>Item</b>	<b>Class of transmitter</b>	<b>Permitted operating frequency band (MHz) (lower limit exclusive, upper limit inclusive)</b>	<b>Maximum EIRP</b>	<b>Limitations</b>
42	Radiofrequency identification transmitters	(a) 1.77–2.17 (b) 2.93–3.58 (c) 7.2–10.01	100 pW	
43	Radiofrequency identification transmitters	(a) 13.553–13.567 (b) 915–925 (c) 2400–2450 (d) 5725–5795 (e) 5815–5875 (f) 24000–24250	1 W	
44	Radiofrequency identification transmitters	5795–5815	2 W	
45	Radiofrequency identification transmitters	920–926	4 W	(a) The transmitter must comply with the instrument known as ISO/IEC 18000-6c. (b) Emissions in the band below 917.75 MHz must be no greater than –37 dBm EIRP.

				<p>(c) Emissions above 926 MHz must be no greater than –33 dBm EIRP.</p> <p>(d) The transmitter must not be used unless more than 1 W EIRP is necessary to achieve satisfactory system performance.</p>
46	Radiofrequency identification transmitters	<p>(a) 22000–23480</p> <p>(b) 24100–26500</p>	630 mW	<p>(a) The transmitter must only be operated indoors.</p> <p>(b) The transmitter must not be operated within a nominated distance of a specified Papua New Guinean radioastronomy site.</p>

47	Transmitters used for underground communications	<p>(a) 31–32</p> <p>(b) 33–34</p> <p>(c) 35–36</p> <p>(d) 37–38</p> <p>(e) 42–43</p> <p>(f) 44–45</p> <p>(g) 70.24375–74.8</p> <p>(h) 75.2–77.29375</p> <p>(i) 77.49375–84.69375</p> <p>(j) 149.25–149.9</p> <p>(k) 150.05–151.39375</p> <p>(l) 152.49375–156</p> <p>(m) 157.45–160.6</p> <p>(n) 160.975–161.475</p> <p>(o) 162.05–173.29375</p> <p>(p) 403–406</p> <p>(q) 406.1–420</p>	See limitation	The maximum EIRP is 3.5 nW, at an aboveground opening associated with the underground communications.
----	--	--	----------------	---

		(r) 450–500.99375 (s) 504.99375–510.99375 (t) 514.99375–520		
48	Transmitters used for underground communications	(a) 0.5265–1.605 (b) 87.5–108 (c) 174–230 (d) 520–694	See limitation (a)	(a) The maximum EIRP is 10 $\mu$ W, for emissions from an above-ground opening associated with the underground environment.  (b) The transmitter must be used primarily for the augmentation of an above-ground broadcasting service in underground tunnels.
49	Personal alarm transmitters	27.5–27.51	100 $\mu$ W	
50	Transmitters used with personal alarm transmitters	27.5–27.51	500 mW	Each transmission must not exceed 4 seconds over a 60-second period.
51	Alarm transmitters (including security and Personal safety transmitters)	303.6–304.05	1 mW	(a) The maximum EIRP is 100 $\mu$ W unless the transmitter is manually activated with a limited activation period no greater than 10 seconds.  The average EIRP must not exceed 100 $\mu$ W in any 10-second period.
52	Home detention monitoring equipment transmitters	314.075–314.325	200 $\mu$ W	In a 10 second period, a single transmission must not exceed 10 milliseconds.

53	Alarm transmitters	344.8–345.2	1 mW	The average EIRP must not exceed 100 $\mu$ W: (a) if the length of a pulse train does not exceed 0.1 seconds – in the length of one complete pulse train; (b) if the length of a pulse train exceeds 0.1 seconds – in the 0.1 second period during which the EIRP is at its maximum value; or (c) if the transmitter operates for more than 0.1 seconds – in the 0.1 second period during which the EIRP is at its maximum value.
----	--------------------	-------------	------	--

**Frequency hopping, Wi-Fi and RLAN transmitters**

<b>Item</b>	<b>Class of transmitter</b>	<b>Permitted operating frequency band (MHz) (lower limit exclusive, upper limit inclusive)</b>	<b>Maximum EIRP</b>	<b>Limitations</b>
54	Frequency hopping transmitters	915–928	1 W	A minimum of 20 hopping frequencies must be used.
55	Frequency hopping transmitters	2400–2483.5	500 mW	Either: (a) the transmitter must meet the requirements of ETSI EN 300 328; or (b) a minimum of 15 hopping frequencies must be used.

56	Frequency hopping transmitters	2400–2483.5	4 W	A minimum of 75 hopping frequencies must be used.
57	Frequency hopping transmitters	5725–5850	4 W	A minimum of 75 hopping frequencies must be used.
58	Digital modulation transmitters	915–928	1 W	(a) The radiated peak power spectral density in any 3 kHz must not exceed 25 mW per 3 kHz. (b) The minimum 6 dB bandwidth must be at least 500 kHz.
59	Digital modulation transmitters	2400–2483.5	4 W	(a) The radiated peak power spectral density in any 3 kHz must not exceed 25 mW per 3 kHz. (b) The minimum 6 dB bandwidth must be at least 500 kHz.
60	Digital modulation transmitters	5725–5850	4 W	(a) The radiated peak power spectral density in any 3 kHz must not exceed 25 mW per 3 kHz. (b) The minimum 6 dB bandwidth must be at least 500 kHz.
61	Radio Local Area Network transmitters	5150–5250	200 mW (averaged over the entire transmission burst)	(a) The transmitter must only be used indoors. (b) The power spectral density of a transmitter with a bandwidth greater than or equal to 1 MHz must not exceed 10 mW EIRP per MHz. (c) The power spectral density of a transmitter with a bandwidth less than 1 MHz must not exceed 40 $\mu$ W EIRP per 4 kHz.

62	Radio Local Area Network transmitters	5250–5350	200 mW (averaged over the entire transmission burst)	<p>(a) The transmitter must only be used indoors.</p> <p>(b) The power spectral density of a transmitter with a bandwidth greater than or equal to 1 MHz must not exceed 10 mW EIRP per MHz.</p> <p>(c) The power spectral density of a transmitter with a bandwidth less than 1 MHz must not exceed 40 <math>\mu</math>W EIRP per 4 kHz.</p> <p>(d) The transmitter must use Dynamic Frequency Selection (DFS).</p> <p>(e) If the maximum EIRP is greater than 100 mW, the transmitter must use Transmit Power Control (TPC).</p>
63	Radio Local Area Network transmitters	(a) 5470–5600 (b) 5650–5725	1 W (averaged over the entire transmission burst)	<p>(a) The maximum radiated mean power density must not exceed 50 mW/MHz EIRP in any 1 MHz band.</p> <p>(b) The transmitter must use Dynamic Frequency Selection (DFS).</p> <p>(c) If the maximum EIRP is greater than 500 mW, the transmitter must use Transmit Power Control (TPC).</p>

63A	Radio Local Area Network transmitters (Low Power RLAN (Wi-Fi 6E/7))	5925 – 6425	25 mW	<p>Very Low Power (VLP) devices:</p> <ul style="list-style-type: none"> <li>(a) for outdoor use;</li> <li>(b) must implement a contention-based protocol as defined in clause 5;</li> <li>(c) must not exceed a PSD of 1.25 mW EIRP per 1 MHz;</li> <li>(d) any emissions in any 1 MHz band wholly below 5925 MHz must not exceed -37 dBm EIRP;</li> <li>(e) must comply with the standards prescribed in Schedule 2, item 18.</li> </ul>
			250 mW	<p>Low Power Indoor (LPI) devices:</p> <ul style="list-style-type: none"> <li>(a) must be designed and configured to operate Indoor only;</li> <li>(b) must use contention-based protocol for multiple access as defined in clause 5;</li> <li>(c) must not exceed PSD of 12.5mW per 1 MHz;</li> <li>(d) Any emissions in any 1 MHz band wholly below 5925 MHz must not exceed -27 dBm EIRP; and</li> <li>(e) The transmitter must comply with the standards as prescribed in Schedule 2, item 18.</li> </ul>

64	Data communications transmitters used outdoors	59000–63000	150 W	<p>(a) The transmitter must not be operated on board an aircraft.</p> <p>(b) The maximum transmitter power must not exceed 20 mW.</p> <p>(c) The transmitter must not cause spurious emissions outside the band at or greater than – 30 dBm/MHz.</p> <p>(d) The transmitter must only be used outdoors.</p>
65	Data communications transmitters used outdoors	57000–66000	20 W	<p>(a) The average power density of any emission must not exceed 9 uW/cm<sup>2</sup> at a distance of 3 metres.</p> <p>(b) The peak power density of any emission must not exceed 18 uW/cm<sup>2</sup> at a distance of 3 metres.</p> <p>(c) The transmitter must not cause spurious emissions outside the band at or greater than – 30dBm/MHz.</p> <p>(d) The transmitter must only be used in a building or enclosed structure. Federal Register</p>

<b>Radiodetermination – sensors using radar for measurement</b>				
<b>Item</b>	<b>Class of transmitter</b>	<b>Permitted operating frequency band (MHz) (lower limit exclusive, upper limit inclusive)</b>	<b>Maximum EIRP</b>	<b>Limitations</b>
66	Radiodetermination transmitters	24000–24250	1 W	
67	Radiodetermination transmitters	60000–61000	20 mW	
68	Radiodetermination transmitters operated in radio frequency shielded enclosures	(a) 5250–7000 (b) 8500–10600 (c) 24050–26500 (d) 75000–85000	75 nW	(a) The maximum EIRP applies outside the shielded room enclosure. (b) The transmitter must meet the requirements of ETSI Standard EN 302 372.
69	Radiodetermination transmitters	76000–77000	25 W	
70	Radiodetermination transmitters	77000–81000	See limitations	(a) The transmitter must meet the requirements of ETSI Standard EN 302 264. (b) The transmitter must not be operated within a nominated distance of a specified Papua New Guinean radioastronomy site.
71	Radiodetermination transmitters	75000–85000	See limitations	(a) The transmitter must be operated in a position such that emissions are directed towards: (i) the ground; or (ii) the floor or a wall of a building or similar structure.

				<p>(b) The transmitter must comply with ETSI Standard EN 302 729.</p> <p>(c) The transmitter must not be operated within a nominated distance of a specified Papua New Guinean radioastronomy site.</p>
--	--	--	--	---

<b>Other applications</b>				
72	In-store pricing system transmitters	0.0366–0.0402	4.8 W	The transmitter must only be used indoors.
73	In-store DAB repeater transmitters	174–230	10 $\mu$ W	<p>(a) The maximum EIRP applies to emissions measured outside the building.</p> <p>(b) The transmitter must only be used for the augmentation of cochannel DAB broadcasting services operating in the area.</p>
74	Aquatic animal tracking transmitters	48–49	10 mW	
75	Video sender transmitters	529–694	12 $\mu$ W	
76	Ultra-wideband short-range vehicle radar system transmitters	22000–26500	See limitations	<p>(a) The transmitter must meet the requirements of ETSI Standard EN 302 288.</p> <p>(b) The transmitter must not be operated within a nominated distance of a specified Papua New Guinean radioastronomy site.</p>
77	Infrared transmitters	187.5 THz – 420 THz	125 mW (output power)	

78	Ultra-wideband transmitters	(a) 3400–4800 (b) 6000–8500	See limitations	<p>(a) The transmitter must comply with either:</p> <ul style="list-style-type: none"> <li>(i) ETSI Standard EN 302 500; or</li> <li>(ii) ETSI Standard EN 302 065.</li> </ul> <p>(b) The transmitter must not be operated on board any aircraft or from any fixed outdoor location.</p> <p>(c) The transmitter must not be operated in the 3425-3575 MHz band before 14 December 2015.</p> <p>(d) The transmitter must not be operated within a nominated distance of a specified Papua New Guinean radioastronomy site.</p> <p>(e) The transmitter must not be operated in the 8400–8500 MHz band within the nominated distance of a specified SRS earth station.</p>
79	In-ground ultrawideband transmitters	4200–4800	–62 dBm/MHz	<p>(a) The transmitter must comply with Part 2 of ETSI Standard EN 302 065.</p> <p>(b) The transmitter must not be operated within a nominated distance of a specified Papua New Guinean radioastronomy site.</p>

**NOTE 1 :** A transmitter that complies with the field strength limit of  $2400/F(\text{kHz}) \mu\text{V}/\text{M}$  at a distance of 300 metres, contained in ETSI EN 300 330 (V2.1.1) — "Short Range Devices (SRD); radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems 9 kHz to 30 MHz (see especially Annex J for 148.5 kHz → 30 MHz limits and the transmitter conformance clauses), will meet the requirement not to exceed the maximum EIRP specified in items 3, 4, 5, 6 and 7.

**NOTE 2 :** The systems and associated medical implant communications systems transmitters mentioned in items 33 and 34 are devices that require marketing approval from the Therapeutic Goods Administration.

## Schedule 2: International instruments that apply to a transmitter

### (1) Using this table

In this table:

- (a) a reference to a number in column 1 is a reference to an item in the table in Schedule 1, and to all the transmitters that are operated in accordance with that item;
- (b) a reference to a number in column 2 is a reference to the number given to an instrument by the entity that produced the instrument.

**Table—Instruments that apply to a transmitter**

	<b>Transmitter</b>	<b>Instrument that applies to the transmitter</b>	<b>Name of the instrument</b>	<b>Entity that produced the instrument</b>
1	30	EN 300 422-1	Electromagnetic compatibility and radio spectrum Matters (ERM); Wireless microphones operating in the 25MHz to 3GHz frequency range.	ETSI
2	31	EN 301 357	Electromagnetic compatibility and radio spectrum Matters (ERM); Cordless audio devices in the range 25 MHz to 2 000 MHz.	ETSI
3	31	EN 300 422	Electromagnetic compatibility and radio spectrum Matters (ERM); Wireless microphones operating in the 25MHz to 3GHz frequency range.	ETSI

4	33	EN 301 839	Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Ultra Low Power Active Medical Implants (ULP-AMI) and Peripherals (ULP-AMI-P) operating in the frequency range 402 MHz to 405 MHz;	ETSI
5	34	EN 302 537	Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Ultra Low Power Medical Data Service Systems operating in the frequency range 401 MHz to 402 MHz and 405 MHz to 406 MHz;	ETSI
6	55	EN 300 328	Electromagnetic compatibility and radio spectrum Matters (ERM); Wideband transmission systems; Data transmission equipment operating in the 2,4 GHz ISM band and using wide band modulation techniques	ETSI
7	68	EN 302 372	Electromagnetic compatibility and radio spectrum matters (ERM); Short Range Devices (SRD); Equipment for Detection and Movement; Tanks Level Probing Radar (TLPR) operating in the frequency bands 5,8 GHz, 10 GHz, 25 GHz, 61 GHz and 77 GHz	ETSI

8	70	EN 302 264	Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Road Transport and Traffic Telematics (RTTT); Short Range Radar equipment operating in the 77 GHz to 81 GHz band	ETSI
9	71	EN 302 729	Electromagnetic compatibility and radio spectrum Matters (ERM); Short Range Devices (SRD); Level Probing Radar (LPR) equipment operating in the frequency ranges 6 GHz to 8,5 GHz, 24,05 GHz to 26,5 GHz, 57 GHz to 64 GHz, 75 GHz to 85 GHz	ETSI
10	76	EN 302 288	Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Road Transport and Traffic Telematics (RTTT); Short range radar equipment operating in the 24 GHz range	ETSI
11	78	EN 302 065	Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD) using Ultra Wide Band technology (UWB)	ETSI

12	78	EN 302 500	Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD) using Ultra WideBand (UWB) technology; Location Tracking equipment operating in the frequency range from 6 GHz to 9 GHz	ETSI
13	79	EN 302 065	Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD) using Ultra Wide Band technology (UWB)	ETSI
14	45	ISO/IEC 18000-6c:2013	Information Technology – Radio frequency identification for item management – Part 6: Parameters for air interface communications at 860 MHz to 960 MHz General	International Organization for Standardisation (ISO)
15	39	ETSI EN 300 330 (V2.1.1)	"Short Range Devices (SRD); radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems 9 kHz to 30 MHz	ETSI
16	33	ETSI EN 301 839 and ETSI EN 302 537	MedRadio / medical-device radio equipment test and emission requirements applicable to the 401–406 MHz MedRadio band (use the appropriate Parts/annexes for transmitter bandwidth, power and unwanted-emissions limits).	ETSI
17	33	ETSI EN 302 537 (V2.1.1 or later)	Ultra Low Power Medical Data Service (MEDS) systems (401–402 MHz / 405–406 MHz). See	ETSI

			radiated measurement clauses and Annex B.	
18	63A	ETSI EN 303 687	Harmonised Standard for access to radiofrequency spectrum	ETSI

**Note 1:** An entry in column 3 is the title of an instrument and is included for information only.

**Note 2:** An entry in column 4 is the name of the entity that produced the instrument and is included for information only.

**Note 3:** Copies of instruments produced by ETSI are available from the ETSI website: <http://www.etsi.org>.

**Note 4:** Copies of instruments produced by the International Organization for Standardisation are available from the following website: <http://www.saiglobal.com>.